

**Passenger Elevators** Platform dimensions up to 10'-0" wide by 8'-0" deep (305 cm wide by 244 cm deep)

Elevator Capacity Load	Elevator Speed Range							
	Up to 500 fpm (2.5 m/s)		600-800 fpm (3.0-4.0 m/s)		1,000-1,200 fpm (5.0-6.0 m/s)		1,400 fpm (7.0 m/s) and faster	
	Car	Counterweight	Car	Counterweight	Car	Counterweight	Car	Counterweight
< 3,000 lbs. (1,350 kg.)	Model <b>B</b>	Model <b>D</b>	Model <b>A</b>	Model <b>C</b>	Express <b>3</b>	Model <b>C</b>	Express <b>6</b>	Model <b>A</b>
3,500 lbs. (1,600 kg.)	Model <b>B</b>	Model <b>D</b>	Model <b>A</b>	Model <b>C</b>	Express <b>3</b>	Model <b>C</b>	Express <b>6</b>	Model <b>A</b>
4,000 lbs. (1,800 kg.)	Model <b>B</b>	Model <b>D</b>	Model <b>A</b>	Model <b>C</b>	Express <b>3</b>	Model <b>C</b>	Express <b>6</b>	Model <b>A</b>
4,500 lbs. (2,050 kg.)	Model <b>A</b>	Model <b>C</b>	Model <b>A</b>	Model <b>C</b>	Express <b>3</b>	Model <b>C</b>	Express <b>6</b>	Model <b>A</b>
5,000 lbs. (2,300 kg.)	Model <b>A</b>	Model <b>C</b> with adjustable stops	Model <b>A</b>	Model <b>C</b> with adjustable stops	Express <b>3</b>	Model <b>C</b>	Express <b>6</b>	Model <b>A</b>
6,000 lbs. (2,700 kg.)	Model <b>A</b>	Model <b>C</b> with adjustable stops	Model <b>A</b>	Model <b>C</b> with adjustable stops	Express <b>6</b>	Model <b>A</b>	Express <b>6</b>	Model <b>A</b>
7,000 lbs. (3,200 kg.)	Model <b>A</b>	Model <b>C</b> with adjustable stops	Model <b>A</b>	Model <b>C</b> with adjustable stops	Elevators in this high speed and capacity range often involve additional complexities that you should discuss with an ELSCO guide specialist previous to ordering.			
Up to 300 fpm (1.5 m/s)								
8,000-10,000 lbs. (3,600-4,500 kg.)	Model <b>A</b> with red polyurethane rollers	Model <b>C</b> with red polyurethane rollers & adjustable stops						

**Hospital Elevators** Platform dimensions up to 6'-0" wide by 10'-0" deep (183 cm wide by 305 cm deep)

Elevator Capacity Load	Elevator Speed Range							
	Up to 250 fpm (1.25 m/s)		300-500 fpm (1.5-2.5 m/s)		600-800 fpm (3.0-4.0 m/s)		1,000-1,200 fpm (5.0-6.0 m/s)	
	Car	Counterweight	Car	Counterweight	Car	Counterweight	Car	Counterweight
< 3,000 lbs. (1,350 kg.)	Model <b>B</b>	Model <b>D</b>	Model <b>B</b>	Model <b>D</b>	Model <b>A</b>	Model <b>C</b>	Express <b>3</b>	Model <b>C</b>
3,500 lbs. (1,600 kg.)	Model <b>B</b>	Model <b>D</b>	Model <b>A</b>	Model <b>D</b>	Model <b>A</b>	Model <b>C</b>	Express <b>3</b>	Model <b>C</b>
4,000 lbs. (1,800 kg.)	Model <b>A</b>	Model <b>D</b>	Model <b>A</b>	Model <b>D</b>	Model <b>A</b>	Model <b>C</b>	Express <b>3</b>	Model <b>C</b>
4,500 lbs. (2,050 kg.)	Model <b>A</b>	Model <b>C</b>	Model <b>A</b>	Model <b>C</b>	Model <b>A</b>	Model <b>C</b>	Elevators in this high speed and capacity range often involve additional complexities that you should discuss with an ELSCO guide specialist previous to ordering.	
5,000 lbs. (2,300 kg.)	Model <b>A</b>	Model <b>C</b> with adjustable stops	Model <b>A</b>	Model <b>C</b> with adjustable stops	Model <b>A</b>	Model <b>C</b> with adjustable stops		
6,000 lbs. (2,700 kg.)	Model <b>A</b> with green polyurethane rollers	Model <b>C</b> with green polyurethane rollers & adjustable stops	Model <b>A</b> with green polyurethane rollers	Model <b>C</b> with green polyurethane rollers & adjustable stops				
7,000 lbs. (3,200 kg.)	Model <b>A</b> with green polyurethane rollers	Model <b>C</b> with green polyurethane rollers & adjustable stops	Model <b>A</b> with green polyurethane rollers	Model <b>C</b> with green polyurethane rollers & adjustable stops				
8,000-10,000 lbs. (3,600-4,500 kg.)	Model <b>A</b> with red polyurethane rollers	Model <b>C</b> with red polyurethane rollers & adjustable stops						

**Service and Freight Elevators** Platform dimensions up to 10'-0" wide by 8'-0" deep (305 cm wide by 244 cm deep)

Elevator Capacity Load	Elevator Speed Range							
	Up to 250 fpm (1.25 m/s)		300-500 fpm (1.5-2.5 m/s)		600-800 fpm (3.0-4.0 m/s)		1,000-1,200 fpm (5.0-6.0 m/s)	
	Car	Counterweight	Car	Counterweight	Car	Counterweight	Car	Counterweight
< 3,000 lbs. (1,350 kg.)	Model <b>B</b>	Model <b>D</b>	Model <b>B</b>	Model <b>D</b>	Model <b>A</b>	Model <b>C</b>	Express <b>3</b>	Model <b>C</b>
3,500 lbs. (1,600 kg.)	Model <b>B</b>	Model <b>D</b>	Model <b>A</b>	Model <b>D</b>	Model <b>A</b>	Model <b>C</b>	Express <b>3</b>	Model <b>C</b>
4,000 lbs. (1,800 kg.)	Model <b>A</b>	Model <b>D</b>	Model <b>A</b>	Model <b>C</b>	Model <b>A</b>	Model <b>C</b>	Express <b>3</b>	Model <b>C</b>
4,500 lbs. (2,050 kg.)	Model <b>A</b>	Model <b>C</b>	Model <b>A</b>	Model <b>C</b>	Model <b>A</b>	Model <b>C</b>	Elevators in this high speed and capacity range often involve additional complexities that you should discuss with an ELSCO guide specialist previous to ordering.	
5,000 lbs. (2,300 kg.)	Model <b>A</b>	Model <b>C</b> with adjustable stops	Model <b>A</b>	Model <b>C</b> with adjustable stops	Model <b>A</b>	Model <b>C</b> with adjustable stops		
6,000 lbs. (2,700 kg.)	Model <b>A</b> with green polyurethane rollers	Model <b>C</b> with green polyurethane rollers & adjustable stops	Model <b>A</b> with green polyurethane rollers	Model <b>C</b> with green polyurethane rollers & adjustable stops				
8,000 lbs. (3,600 kg.)	Model <b>A</b> with green polyurethane rollers	Model <b>C</b> with green polyurethane rollers & adjustable stops	Model <b>A</b> with green polyurethane rollers	Model <b>C</b> with green polyurethane rollers & adjustable stops				
10,000 lbs. (4,500 kg.)	Model <b>A</b> with red polyurethane rollers	Model <b>C</b> with red polyurethane rollers & adjustable stops						

**Note:** Unless otherwise specified, the guides recommended in the charts above should be equipped with ride quality-optimizing neoprene composition roller wheels.